



# RS232 to Multi-Mode Fiber Converter



## FEATURES

- Converts RS232 to Multi-Mode fiber
- Bi-directional
- 9-Pin DTE pinout for RS232
- Compact Size: 1" x 2.5" x 3"
- DC power input or DC adapter power
- 12, 24 or 48 VDC power supply
- Under 1 watt (measured 70 ma @ 12VDC)
- Industrial Temperature Rated -40 to +85 C
- -34.4 dB Receive Sensitivity, 2 Km range
- -16 minimum transmit level
- Use with 50/125, 62.5/125, 100/140 fiber
- Data rates of 0 to 230.4 Kbps
- Provides noise and ground loop immunity for serial circuits

Typical application is from one RS232 device to another RS232 device over Multi-Mode fiber. Typical performance is -34.4 dbM receive sensitivity, 2 km distance with 62.5/125 fiber cable. Control leads are *not* passed through or converted.

On the interface converter, the green connector is DC power, the 9-pin connector is RS232. Pin 2 is Receive Data, data into the adapter, pin 3 is Transmit Data, data out of the adapter, and pin 5 is Signal Ground. Pin 7, RTS, has a positive voltage out of the unit. These pins are identical to those on a 9-pin pc interface. All the other pins on the 9-pin connector are ignored.

Several cable adapters are available for connecting the unit to other devices.

Part #	Description	Price
9802012	PC Direct DE9S to RJ45, use with 9802014	\$12
9802014	PC Remote DE9S to RJ45 use with 9802012	\$12
9801033	DE9S to DE9S null modem cable	\$6
9801009	DE9S to DB-25P PC to modem cable	\$12

## DESCRIPTION

The DCB RS232 to Multi-Mode fiber optic converter is a compact 1" high by 2.5" wide by 3" long. The converter is externally powered, available in a 12 volt, 24 volt or 48 volt version. All of these units are wide industrial temperature rated.

The unit bidirectionally converts RS232 to Multi-Mode fiber.

## SPECIFICATIONS

### Connectors:

- 3-wire power connector (+, -, Fr Ground)
- Multi-mode ST fiber, 1 Tx, 1 Rx fiber
- 9-pin RS232 connector, DTE data (pins 2 and 3) and ground (pin 5), positive RS232 voltage on pin 7, RTS
- 1" x 2.5" x 3"
- 40 to +85 C operation

### How to Order

Part #	Description	Price
9802087	9-19 VDC powered adapter, <i>no power supply included</i> , Temperature Rated -40 C to +85 C	\$279
9001156	120VAC to 12 VDC supply	\$14
9802088	18-36 VDC powered adapter, <i>no power supply included</i> , Temperature Rated -40 C to +85 C	\$279
9802089	36-72 VDC powered adapter, <i>no power supply included</i> , Temperature Rated -40 C to +85 C	\$279



**Data Comm for Business, Inc.**

**2949 CR 1000 E**

**Dewey, IL 61840**

**Voice 8004DCBNET  
(800.432.2638)**

**Fax 217.897.1331**

**Email [info@dcbnet.com](mailto:info@dcbnet.com)**

**Web <http://www.dcbnet.com>**

